GUHRING



Induction Shrink Fit Systems

Work easily, quickly and efficiently ...

GSS 3001

Fume extraction

Vapours produced during the shrink fit process are removed and filtered under controlled conditions by the fume extraction system.

Length setting

During the shrink fit process the tool is pre-set to the required length with the assistance of an adjustment rod.

Quick cooling

The water-cooled cooling elements cool down the shrink fit chuck quickly and safely. The shrink fit chuck remains clean and dry, so that it can be applied again without drying and without rusting. Hot spots remain safely screened during the cooling process in order to prevent burns.

The advantages of shrink fit technology:

- Perfect 360° tool clamping provides extreme clamping force and rigidity
- High repeatability
- Minimal imbalance thanks to rotational symmetry
- Excellent concentricity for symmetrical cutting edge loading therefore longer tool life
- Reduced components, therefore lower costs for purchasing, storage and administration

You benefit from:

- High economic efficiency thanks to effective mode of operation
- Full transparency due to process analysis
- Absolutely user-friendly

... with each application!



User-friendly software

Intuitive menu navigation similar to the wellestablished Guhring TM-Software GTMS via touch-screen monitor (for details see page 5).

Safe shrink fitting

The minimal heating of the shrink fit chuck ensures maximum operating safety on the one hand, on the other the controlled heating ensures the long life of the shrink fit chuck.

Tool identification Balluff chip

The read and write function of the Balluff chip simplifies tool identification.

Tool life can be managed.

GSS 3001

GÜHRING

Label printer

Print data such as Guhring no., current setting dimension, date, operator etc. on an adhesive label for your pre-set tool.

Important features:

- > Setting, shrink fitting and measuring with one system
- > Operating system WIN 7
- > Stable Beckhoff control system with touch-screen and foil keyboard
- > Compact, workshop suited and robust design
- > Ergonomic arrangement of all operating elements for comfortable handling
- > Label printer for providing pre-set tools with information such as Guhring no., setting dimension, Barcode, and much more...
- > Setting and measuring accuracy 0.02 mm

"Everything has its place"

Stop plates for every diameter are accessibly stored directly on the guide column.

"Good accessibility"

Good accessibility to all machine components provides excellent conditions for cleaning and maintenance purposes, i.e. re-filling coolant by simple opening of drawer.

Economic: The Speedcooler switches off automatically when not in use for a longer period of time.





GSS Software performance features:

- > Intuitive and user-friendly operation thanks to 12" touch-screen and Barcode scanner
- > Comprehensive management possibilities for your tool, holder and shrink fit data as well as the associated parameters
- > Analysis of all processes carried out by system (component, cost centre or user related; setting up to 5 cost centres possible) to optimise your production and for maximum transparency possible
- > Software available in different languages










Additional holder receptacle

Additional mobile receptacle for cooling of holders

ACCESSORIES

2) **Gloves**

Cut and temperature resistant Kevlar gloves, mandatory for all shrink fit applications.



Pliers

For the safe handling of hot tools.

THERMO SECURE

Perfect combination: GSS 3001 + TSG 3000

> perfect concentricity highest balance

maximum operational safety







SPECIAL TOOLING SOLUTIONS

COUNTERSINKING/ DE-BURRING MODULAR TOOLING SYSTEMS

TOOL RESTORATION SERVICE

GUHRING

Gühring oHG

Postfach 100247 • 72423 Albstadt Herderstraße 50-54 • 72458 Albstadt

Tel. +49 74 31 17-0 Fax +49 74 31 17-21279 info@guehring.de www.guehring.de

Your contact: Mathias Hirt

Product Manager Shrink Fit Systems

Tel. +49 74 31 17-25 028 Fax +49 74 31 17-25 666 mathias.hirt@guehring.de



148 812/1354-VII-15 • Printed in Germany • 2013